



KHULNA SHIPYARD LIMITED

BANGLADESH NAVY, KHULNA

PHONE : 02-477720003

E-mail : oiicconf.ksy@gmail.com

BABE (F) – 123/RI&RS/2024-2025/

09 July 2024

Dear Sir

INVITATION FOR QUOTATION OF RUBBER INSULATED & RUBBER SHEATHED FLEXIBLE ELECTRIC CABLE - 4X95MM.

1. Khulna Shipyard Limited (KSY) will procure “Rubber Insulated & Rubber sheathed Flexible Electric Cable - 4X95mm” as per attach specification (01 Page), following terms & condition:
2. Submission of quotation as local supply terms:
 - a) Please send your offer delivery at KSY site basis. Offer should include supply of materials including custom duty, local vat & tax etc within 22/07/2024 (1500 Hours) by e-mail or closed envelop.
 - b) Payment: 100% payment will be made after receiving the material at KSY and satisfactory acceptance after deducting of VAT and TAX.
 - c) Delivery: 45 days from the Purchase Order.
3. 03% (Three) Bid Bond/Earnest Money of the total quoted value must be submit with offer. Bid Bond may be Pay Order/Bank Guarantee in favour of Khulna Shipyard Limited, Khulna.
4. 05% Performance Guarantee (PG) is to be submitted before Purchase Order.
5. Certificate: Supplier must provide manufacturer certificate as regard to the genuinity of the source and items.
6. Offer Validity: 45 Days from Tender Opening Date.

Yours sincerely

Sk. Shah Moshir Rahman
Manager Admin
For Managing Director

ITEM SPECIFICATIONS OF RUBBER INSULATED & RUBBER SHEATHED FLEXIBLE ELECTRIC CABLE - 4X95MM

Purpose:	For power supply to the berth crane
Demand Quantity	160.0 Meter
Country Origin	Italy/ EU countries/ China
Country Manufacture	Italy/ EU countries/ China
Manufacturing Year	-
Brand	Eland cable or equivalent
Size	4 X 95 mm ²
Weight	-
Type:	H07RN-F Neoprene crane cable
Nominal Cross Section Area Of Conductor:	4 X 95 mm ²
Flexibility:	Class 6
Number Of Strand:	To be mentioned
Thickness Of Each Strand:	To be mentioned
Voltage Rating:	600/ 1000 Volt AC
Insulation:	EPR (Ethylene Propylene Rubber)
Outer Sheath:	PCP (Polychloroprene)
Nominal Thickness Of Insulation:	To be mentioned
Nominal Thickness Of Sheath:	To be mentioned
Current Rating:	Min. 225 Amps (At operating temperature 35 ° C)
Conductor:	100% Flexible stranded copper
Outer Sheath Color:	Black
Core Identification Color Code:	Red, Yellow, Blue, Black
Shape:	Round
Standard:	To be mentioned
Necessary Documents:	A catalog of the cable will be submitted with the offer.
Note:	01. There should be no core to core gap inside the cable. 02. Some parts of the cable will be laid under water.